

# PRODUCT DATA SHEET

November, 2009

## EURO MIX TANK UNLINED with COILS

### GENERAL INFORMATION

Vapor tight steel tanks manufactured in Europe and used for blending or suspension of liquids and/or solids while being stored. Tanks have two sealed access hatches on top and one on the driver's side. Top-mounted pressure/vacuum relief valve. Smooth interior walls for easy cleaning. "V" shaped bottom improves drainage efficiency. Bottom-mounted pipe coils for steam heating.

### WEIGHTS AND MEASURES

» <b>Capacity:</b>	.....	68,000 litres (68 m <sup>3</sup> ) 68.000 kilos
» <b>Height:</b>	.....	3180 mm (service) 3380 mm (transport)
» <b>Width:</b>	.....	2505 mm (overall)
» <b>Length:</b>	.....	11500 mm (overall)
» <b>Weight:</b>	.....	14500 kg empty (approx)
» <b>Temperature Limits: (dry resistance)</b>	.....	70° C maximum (NBR)* 100° C maximum (EPDM/Viton) (Continuous limits)
» <b>Viscosity Limit:</b>	.....	254 centipoise (cP)
» <b>Tank Outside Surface Area:</b>	.....	185 m <sup>2</sup>

### STRUCTURAL DESIGN

» <b>Floor:</b>	.....	6 mm S235 carbon steel, "V" bottom sloping from each side to center
» <b>Walls:</b>	.....	6 mm S235 carbon steel
» <b>Top Deck:</b>	.....	6 mm S235 carbon steel
» <b>Wall Frame:</b>	.....	150 mm x 80 mm x 6 mm c-channel, S355 carbon steel
» <b>Floor Frame:</b>	.....	Longitudinal beams with flat plate cross bracing between beams
» <b>Top Frame:</b>	.....	150 mm x 80 mm x 6 mm c-channel, S355 carbon steel.

### SURFACE DETAILS

» <b>Exterior Coating:</b>	.....	Weather and chemical resistant high gloss polyurethane finish (green)
» <b>Interior Coating:</b>	.....	None

### FEATURES

» <b>Valves:</b>	.....	(1) front 6" 150# ANSI drain and (1) rear 4" 150# ANSI drain
» <b>Relief Valve:</b>	.....	(1) Cast aluminum thief hatch, NBR gasket, pressure setting 17 mbar, vacuum setting 1.7 mbar.
» <b>Misc. Pipe Connections:</b>	.....	(1) – front spare inlet/outlet (blinded), 4" 150# ANSI flange (1) – top deck 4" 150# ANSI flange (blinded) for vapor recovery or top fill (1) – top deck 6" 150# ANSI flanged for level gauging device

### FEATURES – con't

» <b>Guardrails:</b>	.....	Along top deck & landing, fold-down square, steel tubing
» <b>Heating Coil:</b>	.....	3" (88.9 x 5.5 mm) steel pipe in continuous serpentine layout; pressure rated to 12 bar; sloped for easy drainage. Heating surface of 7 m <sup>2</sup> . Design temperature is 190 ° C.
» <b>Electric Motors</b>	.....	(4) SEW 7.5 KW, Type CD132M. 230/400V, 50 Hz, 3 phase, 1440 RPM, 25.00/14.30 Amps, 1.0 Service Factor, II 2G EEx de IIC T4 Enclosure.
» <b>Gearboxes:</b>	.....	(4) SEW, Type KF87 AM132S/M. Reduction ratio 19.45:1. (Input speed: 1440 RPM, Output speed: 74 RPM). 60 mm diameter output shafts.
» <b>Mixer Shafts:</b>	.....	(2) 3040, (1) 2203, (1) 2075 mm Long x 60 mm diameter, C35-C.
» <b>Mixer Blades</b>	.....	Long (bottom) Blades: 12 mm thick x 150 mm wide x 432 mm long (992 mm swing path diameter) Short (upper) Blades: 12 mm thick x 150 mm wide x 295 mm long (718 mm swing path diameter)
» <b>Top Entry:</b>	.....	(2) – 600 mm hinged manways with restriction bars; NBR gaskets
» <b>Side Entry:</b>	.....	(1) – 600 mm hinged manway on driver's side of tank; NBR gasket
» <b>Top Access:</b>	.....	Front stairway to access landing
» <b>Tires:</b>	.....	275/70 R22,5 (doubles)
» <b>Suspension:</b>	.....	Air suspension

\* NBR material is standard. EPDM / Viton are optional materials.

### TESTS/CERTIFICATIONS

» <b>Test and Certifications:</b>	.....	<ul style="list-style-type: none"> <li>Approved for road transport throughout the European Union.</li> <li>Quality control inspections Level 1, 2 &amp; 3 on a scheduled basis.</li> <li>Hydrostatic water test after construction and major repairs. Tested to 1.3 specific gravity and 1 psi (69 mbar)</li> <li>Tank is produced according to CE and ATEX 95 : II 2G Ex de IIB T4</li> <li>TÜV NORD: Fertigung überwacht – Entwurf freiwillig geprüft nach DIN 6625 – Hersteller nach AD 2000-HP 0</li> </ul>
-----------------------------------	-------	---



### ELECTRICAL SPECIFICATIONS

» <b>Power Supply and Motor Control:</b>	.....	<ul style="list-style-type: none"> <li>400V, 3 phase regulated voltage &amp; current supply capable of supplying 50 Amp minimum (by customer's ATEX certified personnel).</li> <li>EX II 2G Ex de IIC T4.</li> </ul>
» <b>Cable Specifications:</b>	.....	Cable: 400V, 50 Amp, four core Min. 4x10 mm <sup>2</sup> up to 50 meters Min. 4x16 mm <sup>2</sup> up to 100 meters Max. outside cable diameter is 28 mm

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. No guarantee of accuracy is given or implied because variations can and do exist. NO WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY BAKERCORP, EITHER EXPRESS OR IMPLIED.